


Toyopearl GigaCap[®] Q-650 Resins

(strong anion exchange chromatography resins)



Part Numbers:	21854	Toyopearl GigaCap Q-650M, 75µm, 100mL	21859	ToyoScreen GigaCap Q-650M, 1mL x 6 ea.
	21855	Toyopearl GigaCap Q-650M, 75µm, 250mL	21860	ToyoScreen GigaCap Q-650M, 5mL x 6 ea.
	21856	Toyopearl GigaCap Q-650M, 75µm, 1L	21400	ToyoScreen Column Holder
	21857	Toyopearl GigaCap Q-650M, 75µm, 5L	42194	ToyoScreen Column Holder with fittings
	21858	Toyopearl GigaCap Q-650M, 75µm, 50L		

Product Description

Toyopearl chromatographic resins are comprised of a methacrylic polymer incorporating high mechanical and chemical stability. Resins are available as non-functionalized "HW" series resins for size exclusion separations, and derivatized with surface chemistries for alternative modes of chromatography such as ion exchange, hydrophobic interaction or affinity separations.

Toyopearl GigaCap Q-650 chromatographic resins are designed for anion exchange chromatography. This chromatographic mode separates molecules on the basis of ionic interactions between the sample and the resin. The separation is usually accomplished in buffered aqueous solution with a gradient of increasing ionic strength. Alternatively, pH adjustment may be used for control of elution.

Formulation

72% (v/v) slurry in 20% (v/v) ethanol

This sheet contains the suggested operating conditions and specification ranges for Toyopearl GigaCap Q-650 resins. Lot-specific specifications are included in the Certificate of Analysis (C of A) shipped with the product.

A. OPERATING CONDITIONS

Pressure Drop Across the Column	max. 3 bar (recommended)
Operating Linear Flow Rate	normally 10 – 600 cm/hour (depending on particle size)
Cleaning in Place/Sanitization	0.5mol/L NaOH or 0.1mol/L HCl
Long Term Storage Conditions	20% (v/v) ethanol (shipping solvent)

B. SPECIFICATIONS

Appearance	White resin slurry which settles upon standing
Particle Size Distribution (>80% within range)	50 – 100µm for M-grade
Mean Pore Diameter (base resin)	1000Å
Ion Exchange Capacity	0.15 ± 0.05 meq/mL
Protein Adsorption Capacity	≥ 162 mg/mL (Bovine Serum Albumin)
Bacterial Count	≤ 100 CFU/mL
Endotoxin Concentration	≤ 10.0 endotoxin units/mL
Resin Volume per Container	The indicated volume is the settled resin volume.
Foreign Substance	not observed, no visual evidence
Eluable Matter	≤ 0.2%
Shelf Life Stability	Estimated minimum 10 years

RDS1030_MAY2009

Denmark

MD Scientific is authorized distributor in

Denmark for Tosoh Bioscience

www.md-scientific.dk - info@md-scientific.dk - Tel. 7027 8565

www.tosohbioscience.com

Tosoh Bioscience GmbH

Zettachring 6

D-70567 Stuttgart

Germany

Phone: 0711/13257 0